

OFFICIAL SAPS® MANUAL ADDENDUM V1.1: MANDATORY EXTENDED CLEARANCE AND TRAJECTORY CONTROL® PROTOCOL

Effective Date: November 18, 2025

This Addendum is an integral supplement to the core **Safety Anchor Post System (SAPS®) Manual**. It provides crystal-clear geometric and procedural guidance for anchor installations where the required inbound clearance extends beyond the standard 1'-00" minimum. The foundational engineering commitment is to utilize **Trajectory Control® (TC)** principles to reduce the **Splat Factor** (fall force outcome) to a negligible, non-injurious force.

1. **Mandatory Compliance and Accountability Protocol**

Accountability for the **Patented SAPS® System** is enforced through procedural and documentation mandates.

A. JHA Protocol and Sign-Off Requirements

- **JHA Requirement:** A **Job Hazard Analysis (JHA)** must be formally drafted, thoroughly reviewed, and **signed by all individuals** performing tasks including **installation, removal, working tied off, or jumping the system to a different elevation**.
- **Timing:** JHA review and sign-off must occur **prior to commencement of operation** and **prior to any shift change**.
- **Compliance Integration:** The JHA must adhere to this Addendum and incorporate all applicable **Provincial, local, and company-specific safety policies**.

B. Foundational Performance and Force Reduction

- **Non-Negotiable MFA Limit (General Note #9):** The system **MUST NOT** allow the Fall Arrest Force (MFA) to exceed the **1,000 lb maximum**.
- **Regulatory Compliance:** This performance is engineered to be well below the **OSHA 1,800 lb limit** (29 CFR 1926.502(d)(16)).

2. Contractor & Competent Person Site-Specific Responsibility

The ultimate responsibility for ensuring the system's safety envelope is achieved rests with the **Contractor and the designated Competent Person**. They must integrate the SRL manufacturer's specific guidelines with the SAPS®/TC® requirements based on the project environment.

- **Manufacturer Guideline Mandate:** The Contractor and the Competent Person are jointly responsible for obtaining and **strictly following the guidelines, warnings, and instructions** provided by the **Type 2 SRL Manufacturer**.
- **SRL Use and General Note #5:** When using any Self-Retracting Lifeline (SRL) in this extended clearance application, the contractor **MUST comply with the Vertical Clearance Mandate (General Note #5)**. This requires calculating and ensuring adequate vertical clearance below the worker's tie-off point.
- **Clarity on Clearance Calculation:** The use of the SRL manufacturer's labeled clearance data is acceptable for determining lanyard elongation and deflection factors, **but the final calculation must still account for the safety margin and potential worker height/harness shift as required by General Note #5**.
- **Site-Specific Accommodation:** This includes determining the precise **distance to safely accommodate the end-user** based on the specific work environment (e.g., swing path clearance, obstacles) to fully **fulfill the event of the safety envelope as per the project**.
- **Consequence of Non-Compliance:** **Failure to confirm adequate vertical clearance nullifies the protective guarantee** and voids the sub-1,000 lb MFA calculation.

3. Extended Clearance Geometry and Structural Requirements

The system's low-force performance is the direct result of adhering to these strict geometric and structural specifications.

Requirement	Principle & Rationale
Protective Geometry (Example)	Anchor post must be installed a minimum of 8'-00" horizontally inbound from any leading edge.
	Rationale (Trajectory Control®): This Geometric Constraint limits the Arc of Swing and free fall, ensuring the worker is arrested vertically and remains in a vertical position relative to the platform.
Mandatory Engineering Review	Any clearance >1'-00" MUST be determined by a SAPS Competent Person and confirmed via a formal Engineering Review .
D-ring Specification	D-ring must be forged rated 5,000 lbs and must rotate 360° .
	Rationale: Provides the mandatory 5:1 Safety Factor. 360° rotation prevents side loading, maintaining full capacity.
D-ring Height	D-ring must be positioned 10" from the finish floor .
	Rationale: Standardizes the vertical attachment point for accurate Total Arrest Distance (TAD) calculation.
Substrate Requirement	Concrete substrate must have a minimum compressive strength of 2,500 PSI .
	Rationale: Ensures the base can provide the necessary reaction force to the anchor, preventing structural failure.
Component Adherence	Use of the specifically designated Type 2 SRL is mandatory.
	Rationale: The Type 2 SRL is a critical variable in the dynamic calculation. Substitution voids the protective guarantee.
Installation Method	NO WET SETTING (Cast-in-Place). TSMDA minimum clearance is 12" . Post-Installed Anchors must follow strict Manufacturer Guidelines.

Rationale: Failure to follow structural specifications **VOIDS** the protective outcome.